



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

282D

Manual Flush Bolt for Metal Doors

Applications



PRODUCT SPECIFICATIONS

Bolt:

Backset: 3/4" (19 mm)

Bolt Throw:

3/4" (19 mm)

Box Quantity:

2

Case Quantity:

80

Category:

Flush Bolts & Coordinating Devices

Certifications:

Three-hour fire rating for metal doors up to 4' wide by 10' tall
Meets ANSI 156.16 for L04251

Faceplate:

1" x 6-3/4" (25 mm x 171 mm)

Fasteners:

Eight #8 x 3/4" combo screws, Eight #8 x 1-1/2" combo screws

Finishes:

US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26,
US26D

Guide Plate Height:

2" (51 mm)

Guide Plate Width:

1" (25 mm)

Material:

Brass faceplate with steel components

Mortise Strike Length:

2-1/4" (24 mm x 57 mm)

Mortise Strike Width:

15/16" (24 mm)

Notes:

Priced as each and sold in increments of two
282S strike plate bag and 282P bolt head available
For use on hollow metal/fire rated doors
Non-handed
Bolt heads are adjustable
Bolt head, if required, may be ordered as part 282P

Optional Features:

Rod Length: 18" (457 mm), 25" (635 mm), 30" (762 mm)- Specify
282R

Rod Length:

12" (305 mm) from center of face to corner of door