



## PRODUCT SPECIFICATIONS

For more information visit [www.hagerco.com](http://www.hagerco.com)

# 283D

## Manual Flush Bolt for Wood Composite Doors

### Applications



## PRODUCT SPECIFICATIONS

### Bolt:

Bolt backset 3/4" (19 mm)

### Bolt Throw:

3/4" (19 mm)

### Box Quantity:

2

### Case Quantity:

40

### Category:

Flush Bolts & Coordinating Devices

### Certifications:

1-1/2 hour fire rating on wood doors up to 4' wide by 10' tall. Meets ANSI 156.16 for L04261.

### Fasteners:

Eight #8 x 3/4" combo screws, Eight #8 x 1-1/2" combo screws

### Finishes:

US3, US4, US5, US9, US10, US10B, US15, US15A, US19, US26, US26D

### Flattened Round Bolt Head:

1/2" (13 mm)

### Guide Plate Height:

2" (57 mm)

### Guide Plate Width:

1" (25 mm)

### Material:

Brass faceplate with steel components

### Mortise Lock Width:

15/16" (24 mm)

### Mortise Strike Height:

2-1/4" (57 mm)

### Notes:

Non-handed  
Bolt head rods are adjustable  
For use with wood composite/fire rated doors  
Non-handed  
Bolt head rods are adjustable