



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

3

Round Wrought Door Pull

Applications

- 6" (152 mm) CTC- 3E
- 8" (203 mm) CTC- 3G
- 10" (254 mm) CTC- 3J
- 12" (305 mm) CTC- 3L



PRODUCT SPECIFICATIONS

Box Quantity:
1

Case Quantity:
12

Category:
Pulls

Certifications:
EPD
Meets ANSI A156.6 for J401 Pulls

Clearance:
1- 1/2"

Door Thickness:
1-3/4" (45 mm)

Fasteners:
Two 1/4" - 20 thru bolts with finish washers

Finishes:
US3, US4, US10, US10B, DBZ, US19, US26, US26D, US28,
US32, US32D

Handicap:
2- 1/2" (64 mm) clearance available on special orders. Add prefix
"H" to number (i.e. H3E)

Material:
Aluminum, Brass, Bronze, Stainless Steel

Notes:
Back to Back - See Model 13
If ordered with tempered glass, specify glass thickness and hole
size

Optional Features:
May be combined with a plate to make a pull plate. Other centers
available on special orders. 2-1/2" (64mm) Clearance available on
special orders. Add prefix "H" to number (i.e. H3E)

Projection:
2-1/4" (57 mm)

Pull Clearance:
1-1/2" (38 mm)

Pull Diameter:
3/4" (19 mm)