



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

311H

Push/Pull Hospital Latch

Applications



PRODUCT SPECIFICATIONS

Bolt Diameter:
3/4" (19 mm)

Bolt Throw:
1/2" (13 mm)

Box Quantity:
1

Case Quantity:
10

Category:
Latches & Protective Plates

Certifications:
ANSI A156.2 closest equivalent (bored latch- series 4000- grade 2)

Door Thickness:
1-3/4" (45 mm)

Escutcheons:
3-1/16" x 5" (78 mm x 127 mm)

Finishes:
US26, US26D, US32, US32D

Material:
Zinc, Stainless Steel

Notes:
2-3/4" (70 mm) backset standard, 5" (127 mm) backset optional
Non-handed

Optional Features:
Engraving Handed: A (standard) - "PUSH" down; "PULL" down. B
- "PUSH" up; "PULL" down. C - "PUSH" up, "PULL" up. D - "PUSH"
down, "PULL" up.

Projection:
2-5/8"

Push & Pull Levers:
1-15/16" x 4-1/2" (49 mm x 114 mm)

Strike Size:
1-1/8" x 2-3/4" (57 mm x 29 mm) T-strike and 1-1/4" x 4-7/8" (124
mm x 32 mm) ASA strike are both included