



## 3540 - Privacy (F76A)

### Applications

Standard Duty Commercial



### PRODUCT SPECIFICATIONS

#### Backsets:

- 2-3/4" (70mm)
- 2-3/8" (60mm)
- 3-3/4" (94mm)
- 5" (128mm)

#### Certifications:

- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours "A" label single doors
- UL10C Positive Pressure Rated
- BHMA Certified ANSI A156.2, Series 4000, Grade 2

#### Door Thickness:

- 1-3/8" - 2" (35 mm - 51 mm)

#### Exposed Trim:

- Wrought brass, Bronze, and Stainless steel

#### Finishes:

- US3, US4, US10, US10B, US26 and US26D
- Anti-Microbial coating (US26D finish only)

#### Functions:

- Privacy (F76A)

#### Latchbolt Type:

- 1/2" (13 mm) throw, stainless steel
- 1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate for 2-3/4" (70 mm) backset
- 1" x 2-1/4" (25 mm x 57 mm) faceplate for 2-3/8" (60 mm) backset

#### Lever Options:

- Archer, August and Withnell

#### Lock Chassis:

- Heavy gauge steel, zinc dichromated for corrosion resistance. Thru-posts are removable. Failure to install thru-posts and screws voids BHMA certification, UL rating, and warranty

#### Notes:

- No exposed mounting screws
- Non-handed

#### Options:

- Lead Lining
- Tactile Warning
- Split Finish

#### Rose Diameter:

- 3-11/32" (85 mm)

#### Strikes:

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

#### Warranty:

- Lifetime