



# 420N

## Neoprene Heavy Duty Surface Automatic Door Bottom

### PRODUCT CUT SHEET

PROJECT:
SUBMITTED BY:
DATE:
NOTES:

#### Material

Aluminum Alloy 6063, T5 Temper  
 Synthetic Rubber Polymer Blend: PVC, Nitrile Rubber (NBR), and Chloroprene  
 Closed Cell Advanced Elastomeric Foam  
 Neoprene is Black


- ▶ BHMA Certified to ANSI/BHMA A156.22, 1,000,000 Cycle Test-Grade 1
- ▶ BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- ▶ Very Good Abrasion Resistance, Tensile Strength and Memory
- ▶ Flame Resistant
- ▶ Moisture Resistant
- ▶ Temperature Range -20°F to 200°F
- ▶ Good Resistance to Ozone, Sunlight and Aging
- ▶ Mounts on Push Side of Door
- ▶ Use with a Threshold for Maximum Sealing Capability
- ▶ Nylon Brush Recommended for Carpet Applications Where No Threshold is Provided
- ▶ Specify Exact Net Length Required to Avoid Field Sizing
- ▶ 36" and Longer May Be Cut Up To 4" in the Field, Under 36" Should Not Be Cut in the Field, Order Net Length
- ▶ Minimum Length 11", Maximum Length 60"
- ▶ End Caps Furnished Standard
- ▶ For Half Mortise Applications Specify HM in Item Number Prior to Finish (ie: 420NHMDKB)
- ▶ 7/8" Max Drop

#### Finishes

420NA Anodized Aluminum  
 420NB Gold  
 420NDKB Dark Bronze

#### Options

Lead Insert Available for Radiation Shield - Specify "Lead-Lined"



NGP-GKT-420N-PCS-1220-A