



PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

6000 Series Medium Duty Surface Mount

Grade 2 Medium Duty Overhead Door Holder and
Stop



Applications

- 6015S- Surface friction
- 6016S- Surface stop only
- 6017S- Surface hold open

PRODUCT SPECIFICATIONS

Box Quantity:
1

Case Quantity:
6

Certifications:
BHMA & ANSI 156.8 Compliant
UL/cUL Listed for up to 3 hours (stop only)
UL10C Positive Pressure Rated (stop only)
UL10B Neutral Pressure Rated (stop only)

Door Thickness:
1-3/4" (44 mm) thick door - standard
1-3/8" - 2-1/4" (36 mm - 57 mm) thick door - optional

Fasteners:
Standard screw packet included for wood or metal door and frame
applications

Finishes:
US10B
US32D (for stainless steel)
ALM

Material:
Steel, stainless steel

Mounting Style:
Surface

Notes:
Adjustable arms provide easy installation
Slide track design
Adjustable in the field
Heavy shock absorber spring provides 5° to 7° compression before
dead stop
Special templating upon request
Single acting doors only
Degree of opening is fully adjustable and can be adapted to
changing needs between 85° to 110°

Size:
Size 1 (SZ1) = 20"-33" door
Size 2 (SZ2) = 33"-51" door

Warranty:
Five years