



PRODUCT SPECIFICATIONS
For more information visit www.hagerco.com

790-911

Concealed Leaf, Swing Clear, Door of Any Material

Applications



PRODUCT SPECIFICATIONS

Certifications:
UL, ADA

Wrap-around frame leaf design for easy installation and protection.
Useful for ADA upgrade work.

Clearance:
7/32" hinge side plus standard lockside clearance

Door Reinforcement:
Wood - None required up to 200 lbs. For metal doors, a 1/8" (3 mm) thick reinforcement plate is recommended along the hinge edge for proper thread engagement of the adjustment studs.

Fastener Size:
#10-24 x 5/8" S/S Dril-Kwik® (metal frame), #10-16 x 1-1/4" S/S
Type AB (wood door)

Finishes:
US32D

Fire Rating:
Up to 3 hr. metal and 90 min. wood composite

Frame Reinforcement:
None required to 200 lbs. Heavier weight use 16-gauge channel.

Length:
79", 83", 85", 95", 119"

Length Options:
Standard and Custom

Material:
14 Ga. (0.075") Type 304 Stainless Steel

Maximum Door Length:
10'-0"

Maximum Door Thickness:
1-3/4"

Maximum Door Weight:
300 lbs

Notes:
Any nonstandard length hinge may require a custom hole pattern based on the requested length. Consult Hager Companies to address the field prep for the doors and frames.

Optional Features:
Lead lined hole pattern, Tamper Resistant Hospital Tips (HT), Sheared leaf, Raised Barrel (SWAGED), Wide Throw, Security Studs, Dutch Door Prep (DUTCH), Powder Coat

Special Features:
1/4" diameter Stainless Steel Pin. Dual 6/6 Nylon bearings between each knuckle. Door edge protection lip (both faces of door). Not recommended for doors with a beveled edge on the hinge side.