




PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

BB1279

Applications

For use on medium weight doors or doors requiring medium frequency service.



PRODUCT SPECIFICATIONS

Box Quantity:
3

Case Quantity:
24

Certifications:
ANSI A8112

Electric Modifications:
EMN (Electric Monitor Only), ETW (Electric Through-Wire Only),
ETM (Electric Through-Wire with Monitoring), Quick Connect

Fastener Size - Machine:
1/4-20 x 1/2"

Fastener Size - Wood:
#14 x 1-1/2"

Features:
Two ball bearings. Non-rising removable pin with button tip and plug.

Finishes:
L1, LS, H2H, USP, US3, US4, US10, US10A, US10B, US15, US26,
US26D

Fire Rating:
Complies with NFPA80 requirements for use on fire rated door assemblies

Gauge:
See Sizing Chart Options

H Height:
See Sizing Chart Options

Knuckles:
5

Material:
Steel with Steel Pin

Notes:
Available with reversible hole pattern.

Options:
3-1/2" x 3-1/2" (89 mm x 89 mm) available with reversible hole pattern
NRP (Non-removable pin)
Stamped with UL logo when ordered for export

H Width:
See Sizing Chart Options