Superior noise cancellation with choice of two wearing styles

- Industry-leading noise cancellation. Blocks out 96% of background noise.¹
- Up to 24 hours of talk time. Keep talking with long-lasting battery life.
- Customizable Parrott Button™. Enable fast access to your favorite features including Push-to-Talk.
- Tough, IP54-rated design. Protection against dust and moisture.
- Choice of wearing styles. Both neckband and headband wearing styles are included.
- VoiceControl[™]. Answer or reject calls with just your voice.
- Walk and talk. Up to 300 feet/100 meters wireless range from paired Bluetooth[®] devices.²
- Flexible boom. Adjustable for the best fit.
- Works with most Bluetooth[®] devices. Use our SDK to enable custom experiences.

Engineered for superior communication in high-noise environments

TECHNICAL SPECIFICATIONS

Audio	Speaker	11 mm
	Speaker sensitivity	117.2dB SPL at 1 mW/1 kHz
	Speaker impedance	32 Ω
	Speaker max input power	52 M 50mW
		150-6800 Hz
	Speaker frequency range	bi-directional electret
	Microphone type	
	Microphone frequency range	150-6800 Hz
	Microphone sensitivity	-47dBV/Pa
Ease of use	Paired devices	Up to 8, connected to two at the same time (multipoint)
	Wearing style	Convertible - choose between over-the-head and behind-the-neck
	App. support	BlueParrott App & BlueParrott Updater
	Features	96% noise cancellation ¹ , answer/end/reject call, LED for power / pairing indicator, Advanced Audio Distribution (A2DP) for music, podcast and GPS streaming ² , voice dialing (activate Siri®/Google Assistant [™]) ² , VoiceControl (hands-free answer / ignore), voice guidance, NFC, HD voice, volume up / down, customizable Parrott Button, IP54 water and dust resistant
Battery	Talk time	Up to 24 hours
	Standby time	Up to 500 hours
	Power Nap for extended standby time	N/A
	Charging time	Approx. 3 hours
	Battery capacity	300mA (headset)
	Bluetooth compliance	Bluetooth version 4.1
	Supported Bluetooth profiles	Advanced Audio Distribution (A2DP) v1.3.1, hands-free profile v1.6, headset profile v1.2, phone book access profile (PBAB) v1.1.1
	Supported modes	EDR (2 and 3 Mb), SCO, eSCO, sniff mode
	Security	128 bit encryption
	Operating range	Up to 100 meters (300 feet) ²
	Pairing passkey or PIN	0000
General	Headset and/or charging case weight	Headset - headband: 55 grams (1.95 oz) Headset - neckband: 51 grams (1.79 oz)
	Headset dimensions	L 177 x W 168 x D 63.5 mm (7.0 x 6.6 x 2.5 in)
	Headset - headband dimensions	L 290 x W 134 x D 33 mm (11.4 x 5.3 x 1.3 in)
	Headset - neckband dimensions	L 261 x W 132 x D 33 mm (10.3 x 5.2 x 1.3 in)
	Operating temperature	-10° C to 50° C (14° F to 122° F)
	Storage temperature	-10° C to 85° C (14° F to 185° F)
	Materials	Headset: PC/ABS, PC, silicon rubber, rubber, nylon, POM, stainless steel, foam, leatherette
	- lacenaes	and TPU
	What's in the box	1 BlueParrott C400-XT headset, 1 headband wearing style, 2 neckband (left and right) wearing styles, 1 USB-A to Micro USB charging cable (1 meter/3.3 feet), foam ear cushion, spare microphone windscreen, 12-24vdc vehicle charge, quick start guide, warranty and warning leaflet
	Certification	Bluetooth 4.1, CE, FCC, IC, CEC, RoHS, REACH, TELEC, KCC, RSC
	Warranty	Two-year warranty EMEA & APAC, one-year warranty North America

1 Independently verified by CJS Labs, San Francisco, CA.

2 Device and network dependent.

GN Making Life Sound Better FOR 150 YEARS blueparrott.com

© 2020 GN Audio A/S. All rights reserved.® BlueParrott is a registered trademark of GN Audio A/S.The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by GN Audio A/S is under license.

