

# AXIS C1004-E Network Cabinet Speaker

Audio made smart and easy

AXIS C1004-E allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages. Security staff can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1004-E is a standalone unit that can be placed almost anywhere, which supports a flexible, scalable and cost-effective system. The speaker can be installed indoors or on sheltered exterior of buildings. It can be mounted horizontally or vertically.

- > **All-in-one speaker system**
- > **Connects to standard IT network**
- > **Simple installation with PoE**
- > **Remote health testing**
- > **SD card for audio content storage**



# AXIS C1004-E Network Cabinet Speaker

<b>Models</b>	AXIS C1004-E Network Cabinet Speaker White AXIS C1004-E Network Cabinet Speaker Black	<b>Event triggers</b>	Virtual inputs, AXIS Camera Application Platform (ACAP) Call: DTMF, State changes
<b>Audio management</b>	Software applications for managing and controlling your audio system regardless of its size and complexity: – Included in the product (runs inside the device) is AXIS Audio Manager Edge, offering zone management, content management, content scheduling and health monitoring. Up to 200 speakers and 20 zones are supported (see separate datasheet for more details). – For larger and more advanced systems we recommend AXIS Audio Manager Pro (see separate datasheet).	<b>Event actions</b>	Play audio clip, send SNMP trap, send Auto Speaker Test, status LED File upload via HTTP, network share and email Notification via email, HTTP, HTTPS and TCP
<b>Audio streaming</b>	One-way/two-way with optional half-duplex echo cancellation. Mono.	<b>Built-in installation aids</b>	Test tone verification and identification
<b>Audio encoding</b>	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis $\mu$ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.	<b>General</b>	
<b>Audio input/output</b>	Built-in microphone (can be disabled)	<b>Casing</b>	IP45- and NEMA 3R-rated Plastic and metal casing Colors: White NCS S 1002-B; black For repainting instructions and impact on warranty, contact your Axis partner.
<b>Built-in microphone specification</b>	50 Hz - 16 kHz	<b>Memory</b>	256 MB RAM, 256 MB Flash
<b>Speaker</b>		<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3af Type 1 Class 3 (max 12.95 W)
<b>Enclosure</b>	Two-way bass-reflex type Speaker component: 12 cm (4.72 in) dynamic cone speaker, 2.5 cm (0.98 in) balanced dome tweeter	<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE
<b>Max sound pressure level</b>	96 dB	<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Max. size 64 GB For SD card recommendations see <a href="http://www.axis.com">www.axis.com</a>
<b>Frequency response</b>	60 Hz - 20 kHz	<b>Reliability</b>	Designed for 24/7 operation.
<b>Coverage pattern</b>	130° horizontal by 100° vertical	<b>Operating conditions</b>	-20 °C to 50 °C (4 °F to 122 °F) Humidity 10–85% RH (condensing)
<b>Amplifier</b>		<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Amplifier description</b>	Built-in 6 W Class D amplifier	<b>Approvals</b>	EMC EN 55022 Class A, EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KN24, KCC KN32 Class A, KN35 Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, CNS 13438 Environment IEC/EN 60529 IP45, IEC/EN 62262 IK10, NEMA 250 Type 3R, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14
<b>Network</b>		<b>Dimensions</b>	H x D x W (with bracket): 290 x 200 x 196 mm (11.4 x 7.9 x 7.7 in)
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management	<b>Weight</b>	3.0 kg (6.61 lb)
<b>Supported protocols</b>	IPv4/v6 <sup>b</sup> , HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, SIP (Cisco, Avaya, Asterisk)	<b>Included accessories</b>	Installation Guide, AVHS authentication key, AXIS Camera Station license key, cable shoe, bracket with screws and washers, AXIS Connector Guard A
<b>System integration</b>		<b>Optional accessories</b>	Safety wire kit For more accessories, see <a href="http://www.axis.com">www.axis.com</a>
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> , One-click cloud connection, AXIS Camera Application Platform (ACAP).	<b>Video management software</b>	AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a>
<b>VoIP</b>	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems. Peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPV6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN) Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
<b>Intelligent audio</b>	Auto Speaker Test (verification via built-in microphone)	<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([www.openssl.org](http://www.openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).
- b. Audio synchronization with IPv4 only.

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)