

## AXIS P3904-R Mk II Network Camera

### Onboard HDTV 720p surveillance with Zipstream

AXIS P3904-R Mk II Network Camera is specially designed for video surveillance in vehicles and rolling stock. The compact, discreet, and rugged camera is IP66/IP67-rated, and can withstand tough conditions such as vibration, shock and temperature fluctuations. Optional accessories for outdoor installation and wider field of view available. The camera provides HDTV 720p with WDR and Lightfinder to ensure high image quality in mixed and low-light conditions. Traffic Light mode enables the camera to distinguish traffic light colors in dark scenes. AXIS P3904-R Mk II supports Zipstream, which significantly reduces bandwidth and storage requirements.

- > [Rugged design with EN 50155:2017 Class OT2/ST2 compliance](#)
- > [Compliance with strict standards in transportation industry](#)
- > [WDR - forensic capture and Lightfinder](#)
- > [Zipstream](#)
- > [Traffic Light mode](#)



# AXIS P3904-R Mk II Network Camera

<b>Models</b>	AXIS P3904-R Mk II RJ45 AXIS P3904-R Mk II M12	Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>Camera</b>		<b>General</b>
<b>Image sensor</b>	1/2.9" Progressive scan RGB CMOS	<b>Casing</b>
<b>Lens</b>	3.6 mm, F2.0 Horizontal field of view: 87° Vertical field of view: 47° M12 mount, fixed iris See <b>Optional accessories</b> for exchangeable lenses	Aluminum and polycarbonate casing
<b>Light sensitivity</b>	HDTV 720p 25/30 fps with Lightfinder Color: 0.15 lux at 50 IRE F2.0 Color: 0.06 lux at 30 IRE F2.0 Color: 0.08 lux at 50 IRE F1.2 Color: 0.04 lux at 30 IRE F1.2	<b>Sustainability</b>
<b>Shutter speed</b>	1/32500 s to 2 s	PVC free
<b>Camera angle adjustment</b>	Pan: ±30° Tilt: 15-90° Rotation: ±175°	<b>Mounting</b>
<b>Video</b>		Inside vehicles and rolling stock <sup>c</sup>
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	<b>Memory</b>
<b>Resolution</b>	1280x720 to 160x90	512 MB RAM, 256 MB Flash
<b>Wide dynamic range</b>	WDR - forensic capture	<b>Power</b>
<b>Frame rate</b>	Up to 25/30 fps (50/60 Hz) in all resolutions	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 2.9 W, max 3.6 W
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	<b>Connectors</b>
<b>Image settings</b>	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, text and image overlay, 20 individual privacy mask, mirroring of images, Traffic Light mode	RJ45: male, 10BASE-T/100BASE-TX M12: female, rugged, D-coded with rotatable coupling nut All connectors support PoE
<b>Pan/Tilt/Zoom</b>	Digital PTZ, preset positions, guard tour, control queue	<b>Storage</b>
<b>Network</b>		Support for microSD/microSDHC/microSDXC card and encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, network access control, digest authentication, user access log, centralized certificate management	<b>Operating conditions</b>
<b>Supported protocols</b>	IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>b</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Normal: -40 °C to 60 °C (-40 °F to 140 °F) Maximum (intermittent): 70 °C (158 °F) Arctic Temperature Control: start-up at -40 °C (-40 °F) Humidity: 10-100% RH
<b>System integration</b>		<b>Storage conditions</b>
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile G and ONVIF <sup>®</sup> Profile S, specification at <a href="http://onvif.org">onvif.org</a>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Event conditions</b>	Analytics, time scheduled, edge storage events	<b>Approvals</b>
<b>Event actions</b>	Record video: SD card and network share Upload images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text	EMC EN 55032 Class A, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.05 (E approval), EN 50498, EAC <b>Safety</b> IEC/EN/UL 62368-1, EN 45545, UN ECE R118, parts of NFPA 130 <sup>d</sup> , IS 13252 <b>Environment</b> IEC/EN 61373 Category 1 Class B, IEC/EN 60529 IP66/67, NEMA 250 Type 4X, IEC/EN 62262 IK08, IEC 60721-3-5 Class 5M3 (vibration and shock), EN 50155:2017 Class OT2/ST2 (EN 50155:2007 Class TX), IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78 <b>Network</b> NIST SP500-267
<b>Data streaming</b>	Event data	<b>Dimensions</b>
<b>Built-in installation aids</b>	Pixel counter	Height: 49 mm (1 15/16 in), ø 109 mm (4 3/16 in)
<b>Analytics</b>		<b>Weight</b>
<b>Applications</b>	<b>Included</b> AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, active tampering alarm <sup>b</sup> <b>Supported</b> AXIS Perimeter Defender	RJ45: 241 g (0.53 lb) M12: 248 g (0.55 lb)
		<b>Included accessories</b>
		Installation guide, Windows <sup>®</sup> decoder 1-user license, drill hole template, top cover tool, lens tool, Allen key Resistorx <sup>®</sup>
		<b>Optional accessories</b>
		<b>Lenses</b> 2.1 mm, F2.2: horizontal field of view 147° 2.8 mm, F1.2: horizontal field of view 110° 6 mm, F1.6: horizontal field of view 52° 8 mm, F1.6: horizontal field of view 40° <b>Other</b> AXIS T96B05 Outdoor Housing, AXIS T94D01S Mount Bracket, AXIS T94D02S Curved Mount Bracket, network coupler IP66, network cable coupler indoor For more accessories, see <a href="http://axis.com">axis.com</a>
		<b>Video management software</b>
		AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
		<b>Languages</b>
		English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		<b>Warranty</b>
		5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
		a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com). b. For detection of tampering attempts in static and non-crowded scenes. c. For outdoor applications, use AXIS T96B05 Outdoor Housing. d. ASTM E162 and the non-flaming parts of ASTM E662
		Environmental responsibility: <a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>