

AXIS T94V01C

Back-to-back camera installation made easy

AXIS T94V01C Dual Camera Mount is a highly versatile accessory that allows back-to-back installation of two Axis cameras for panoramic coverage. It is compatible with a wide range of Axis network cameras, including dome cameras, box cameras, and bullet cameras. It can be easily mounted to diverse Axis mounting accessories with 1.5" NPS threaded interface, for mounting on walls, poles, and under ceilings. AXIS T94V01C is IK10 rated for impact resistance, which safeguards it against vandalism. Suitable for both indoor and outdoor use. Note: To ensure physical stability, do not use AXIS T94V01C for single camera installations.

- > [Save time when installing multiple Axis cameras](#)
- > [Drill fewer holes in walls](#)
- > [Compatible with a wide range of Axis cameras and Axis mounts](#)
- > [Robust design and impact resistant](#)
- > [Suitable for indoor and outdoor use](#)



AXIS T94V01C

General	
Supported products	Compatible with a wide range of Axis cameras. For specific models, see the Accessory selector on www.axis.com/products/accessory-selector
Maximum load	10 kg (22 lb)
Cable routing	Internal
Casing	Mount: impact resistant aluminum Cover plates: UV resistant plastic Color: white NCS S 1002-B
Environment	Indoor Outdoor
Sustainability	PVC free
Approvals	Safety IEC/EN/UL 62368-1
Dimensions	Height: 250 mm (9 13/16 in)
	Width: 36 mm (1 17/16 in) Diameter: 200 mm (7 7/8 in)
Weight	800 g (1.8 lb)
Included accessories	Lock nut Cable ties
Required accessories	Axis mounts with 1.5 " NPS thread
Optional accessories	AXIS T91A06 Pipe Adapter 3/4-1.5"
Warranty	3-year warranty, see axis.com/warranty

Environmental responsibility:
axis.com/environmental-responsibility