

DTMO Series

Desktop Mini Consoles



The **SDC Mini Desktop Consoles** provide an economical method of controlling one or two doors. They are available in four switch configurations with Tri-Color LED indicators. When used with a door status or lock status sensor the LED's allow monitoring of door and lock modes. The switches can provide an On / Off function or momentary access control for electromagnetic EMLocks, Shear Locks, Bolt Locks, Delayed Egress Systems, Electrical Exit System, or Electric Strikes.

FEATURES

- The momentary switch can be used to release a single opening. The maintained (On / Off) switch is used as a bypass for keeping the door unlocked for an extended period of time. The tri-color LED displays Green, Red and Amber colors to indicate up to three lock status conditions.
- Choice of heavy duty momentary or maintained operating switches accommodate lock control functions.
- Tri-color LED indicators provide for immediate status indication of door position or lock status when used with lock monitors such as Door Position (DPS) or Bond Sensors (BAS).
- Push button switches provide an aesthetically pleasing appearance and high operational reliability.

MODELS

- | | |
|-----------------|--|
| DTMO-1 | One Momentary Switch and One LED |
| DTMO-2 | Two Momentary Switches and Two LED's |
| DTMOMA-2 | One Momentary, One Maintained Switch and Two LED's |
| DTMA-2 | Two maintained switches and Two LED's |



SWITCH CONTROLS

Common:	White
Normally Open:	Yellow
Normally Closed:	Orange
Tri-Color LED 12 to 24 VDC	
Negative:	Black
Red Illumination Positive:	Red
Green Illumination Positive:	Green
Amber Illumination Positive:	Power red & green wires simultaneously



SPECIFICATIONS

Contact Rating	2 Amp @ 24VDC, SPDT
Input Power	12/24VDC @ 0.02 Amp Required for Each LED
Color	Beige
Dimensions	4.125" W x 3.125" H x 6.25" L

