



MODEL	A	B	C	D	DEPTH
PB3	4.5	2.75	.625	1.375	3
NOTE: FASTENERS NOT SHOWN ALL DIMENSIONS IN INCHES.					

## PUSH BUTTON - MODEL PB3

### Features

- A compact 1" x 1-3/4" push button
- 3 amp DPST contacts (field modify for DPDT)
- Back box is supplied on single gang applications
- 12-24 VDC bi-color illumination is standard
- Alternate action version available
- Narrow stile version available
- Economy non-illuminated version available
- UL Listed contacts

**Operating Temperature**  
0 to 43C [32 to 110F]

### How to Order

<u>Part #</u>	<u>Description</u>
<b>PB3</b>	Push Button Momentary Single Gang
<b>PB3A</b>	Push Button Alternate Single Gang
<b>PB3N</b>	Push Button Momentary Narrow Stile
<b>PB3AN</b>	Push Button Alternate Narrow Stile



### **PUSH BUTTON - MODEL PB3 (cont'd)**

<b>PB3E</b>	Push Button Momentary Single Gang Economy
<b>PB3EA</b>	Push Button Alternate Single Gang Economy
<b>PB3EN</b>	Push Button Momentary Narrow Stile Economy
<b>PB3EAN</b>	Push Button Alternate Narrow Stile Economy

### **Architectural Specifications**

- A. The Push Button shall be produced by an ISO 9001 certified manufacturer.
- B. The Push Button shall be a compact industrial grade 1" by .75" button with protective cowling.
- C. The Button shall be labeled 'EXIT" and shall be green back lit using a multi-chip LED.
- D. A separate red LED shall be provided as an additional indicator.
- E. The LED's shall operate on 12 or 24 VDC (field selectable).
- F. The switch shall be DP/ST (field modifiable to DPDT) and rated at 3 Amps at 12 or 24 VDC.
- G. The switch shall be available in momentary or alternate action, with a Stainless Steel - 630/US32D single gang face plate or narrow stile Stainless Steel - 630/US32D face plate for mullion mounting.