



MODEL	A	B	C	D	DEPTH
PB5	4.5	2.75	.625	1.375	3
NOTE: FASTENERS NOT SHOWN ALL DIMENSIONS IN INCHES.					

PUSH BUTTON - MODEL PB5

Features

- Stainless steel single gang face plate
- 2" Diameter red button
- 10 amp contacts
- DPST (DPDT by adding wires in the field)
- Illuminated or non-illuminated

Operating Temperature
0 to 43C [32 to 110F]



How to Order

<u>Part #</u>	<u>Description</u>
PB5	Push Button 2" Round Red Momentary Illuminated
PB5E	Push Button 2" Round Red Momentary Non-Illuminated

PUSH BUTTON - MODEL PB5 (cont'd)

Architectural Specifications

- A. The Push Button shall be produced by an ISO 9001 certified manufacturer.
- B. The Push Button shall be a 2" diameter red industrial grade button with protective cowling.
- C. The Button shall be labeled 'EXIT" and shall be red back lit using an incandescent bulb.
- D. The LED shall operate on 12 or 24 VDC (field selectable).
- E. The switch shall be DPST and rated at 10 Amps at 12 or 24 VDC.
- F. The push button shall be mounted on a single gang Stainless Steel - 630/US32D face-plate.
- G. The switch shall be available in momentary action in both illuminated and non-illuminated versions.