

YDC200 Series Economy Door Closer





Table of Contents



Contents

Features & Benefits	3
How to Order	4
Dimensions and Applications	5

YDC200 Economy Door Closer

Yale® YDC200 Series Economy Door Closer is a no-fuss, affordable option for aluminum storefront settings and other high volume applications. Certified to meet ANSI/BHMA A156.4, Grade 1, YDC200 Series Door Closers provide a trusty and reliable solution to your commercial space, including retail, office buildings, and more.

Bringing you a dependable door closer at an attractive price point, Yale Works for YouSM.

Features & Benefits





Features

- Adjustable spring size 1-4 (YDC201) or fixed spring size 4 (YDC204)
- Tri-packed: regular, top jamb, or parallel mounting options
- Non-handed
- Cast aluminium body and threaded adjustable arm
- Rack & pinion design
- Independent latch, sweep, and backcheck intensity valves
- Available in two finishes
- 5 year limited warranty

Benefits

- Ideal for a variety of facilities: Well-suited to commercial, aluminum storefront, and hospitality applications
- Ease of product selection: Economical, affordable, no-fuss product offering
- **Great for retrofit applications:** 3/4" by 9-1/16" closer dimensions easily retrofit to a common footprint
- **Reliable:** UL/cUL listed and designed to meet ANSI/BHMA Grade 1 certification standards

How to Order



Please select model number and finish.

Model	Description	Finish
YDC201	Multi-sized Closer – Non-Hold Open	689 or 690
YDC204	Fixed Size 4 Closer – Non-Hold Open	009 01 090

Notes:

- Door closer warranty becomes void if the closer is installed on the exterior side of a door in the exterior wall of a building.
- It is strongly recommended, and may be required on fire door assemblies, that doors having a door closer be hung on ball-bearing or anti-friction hinges or pivots. Consult local authority having jurisdiction.
- Failure to use fasteners supplied with closer may void factory warranty.
- Fasteners for fire/smoke door assemblies must conform to NFPA 80. In some applications additional fasteners may be mandated by NFPA 80 that are not shipped with standard Yale* product, such as sleeve-nuts/sex-nuts or thru bolts and grommet nuts.
- Information provided is based on 1-3/4" (44mm) x 7' (2.13m) standard weight doors swinging to 110°. Other conditions (such as door height or weight; or wind/draft conditions) may require adjustment of spring setting, selection of a larger size closer or different closer.

Finishes



Parts List

Description	Part Number*
Sleeve Nuts (1-3/4" door only)	SN-134
Cover (order by part number)	YDC200COV

^{*}Specify finish when ordering.




Optional cover (YDC200COV)


Dimensions and Applications



Dimensions



Door Closing Latching Cycle



Applications







Regular Arm

Top Jamb

Parallel Arm

Consult factory if door weight exceeds 150 lbs.

Notes



Notes





Trusted every day

Customer Service Phone:

1-800-438-1951

Customer Service Fax:

1-800-338-0965

24/7 Support Phone:

1-855-213-5841

24/7 Support Email:

Support@YaleLock.com

Website:

yalecommercial.com

Email for orders:

orders.yaleus@assaabloy.com

Contact Us

U.S.A.

Yale Locks & Hardware

Address: 225 Episcopal Road Berlin, CT 06037-4004 Tel: 1-800-438-1951 Fax: 1-800-338-0965 yalelocks.com

Canada:

ASSA ABLOY Door Security Solutions Canada

Address: 160 Four Valley Drive Vaughan, Ontario L4K 4T9 Tel: 1-800-461-3007 Fax: 1-800-461-8989 assaabloydss.ca

International:

ASSA ABLOY Americas International

Tel: 1-905-821-7775 Fax: 1-905-821-1429 assaabloyai.com **THE YALE BRAND**, with its unparalleled global reach and range of products, reassures more people in more countries than any other consumer locking solution.

THE ASSA ABLOY GROUP is the world 's leading manufacturer and supplier of locking solutions, dedicated to satisfying end-user needs for security, safety and convenience.

Yale Commercial is a business associated with ASSA ABLOY Access and Egress Hardware Group, Inc., an ASSA ABLOY Group company. Copyright © 2017-2020, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited. Patent pending and/or patent www.assaabloydss.com/patents.

Part of ASSA ABLOY 42957-7/20